

US15C-B

Standalone Barcode Card Reader Time Clock



US15C-B is an innovative standalone barcode card reader designed for Time & Attendance applications.

The 3" TFT screen can vividly display detailed information and verification result.

US15C-B comes standard with TCP/IP, WiFi and RS-232 communication ports.

An additional USB port allows administrator to transfer data when network is unavailable.

ABOUT MIDEX SOFTWARE

Midex Software is a leading provider of online Time and Attendance software and devices. Our cloud-based software supports a variety of devices, ranging from basic, non-biometric card readers, up to more sophisticated biometric time clocks.

Midex Software modernizes the way companies manage time and attendance

- Manage Employee Attendance
- Automate Payroll Processing
- Eliminate Human Error
- Online Time and Attendance Solutions
- Stop Unauthorized Overtime
- Eliminate "Buddy Punching"
- Reduce administrative costs

SOLUTIONS FOR ANY SIZED BUSINESS



Midex Time Control delivers a modern solution to an age-old challenge – tracking and reconciling employee hours – using today's latest technologies.

With 4 cloud-based solutions to choose from, our **Time and Attendance software** scales to any sized business, from our Free Express Edition for small businesses with less than 25 employees, to our most advanced, multi-user Enterprise Edition for companies with multiple locations and thousands of employees.

Visit: MidexTimeAndAttendance.com | Call: 1-888-544-7878 | Email: info@midexsoftware.com



[/TimeAndAttendanceSoftware](https://www.facebook.com/TimeAndAttendanceSoftware)



[/company/midex-software](https://www.linkedin.com/company/midex-software)



[@MidexSoftware](https://twitter.com/MidexSoftware)



Innovative Time and Attendance Solutions



US15C-B

Standalone Barcode Card Reader Time Clock

FEATURES

- Color TFT screen with graphical interface for ease of use
- Stores 10,000 cards and 50,000 transactions
- Reads barcodes and/or PINs
- Built-in bell scheduling
- Built-in Ethernet, WiFi, RS232 and USB ports.
- Built-in USB port allows for manual data transfer when network is unavailable
- Audio-visual indications for acceptance and rejection of valid/invalid identifications

AVAILABLE ADD-ONS

- External Backup Battery
- External PoE converter

SPECIFICATIONS

Size (WxHxD)	5.5 x 6.5 x 1.8 inches (144 x 165 x 46 mm)
Weight	1lb
Packaging (WxHxD)	9 x 10.5 x 3.5 inches
Packaging Weight	3lbs
Power	12V DC 1.5A
Environment	Operating Temp: 32 to 113 °F (0 to 45 °C) Operating Humidity: 20 to 80%
Capacity	Cards - 10,000 Transactions - 50,000
Display	3" TFT LCD Screen
Communications	RS-232 / RS485 Ethernet WiFi USB - host

Visit: MidexTimeAndAttendance.com | Call: 1-888-544-7878 | Email: info@midexsoftware.com

[f](https://www.facebook.com/TimeAndAttendanceSoftware)/TimeAndAttendanceSoftware | [in](https://www.linkedin.com/company/midex-software)/company/midex-software | [t](https://twitter.com/MidexSoftware)@MidexSoftware